

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 1

Compilation date: 03/10/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: VUBA RESIN BOUND PART A

Product code: VBP.118(A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Vuba Building Products Limited
Units B3-B4 Grovehill Industrial Estate
Annie Reed Road
Beverley
HU17 0LF
United Kingdom

Tel: +44 (0) 1482 778 897

Email: buildingproducts@vuba-group.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1482 778 897
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412

Most important adverse effects: Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H412: Harmful to aquatic life with long lasting effects.

Precautionary statements: P273: Avoid release to the environment.

P281: Use personal protective equipment as required.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P502: Refer to manufacturer or supplier for information on recovery or recycling.

[cont...]

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL-2-(1-ETHYLPENTYL)-1,3-OXAZOLIDINE - REACH registered number(s): 01-0000017206-75-####

EINECS	CAS	PBT / WEL	CLP Classification	Percent
425-660-0	165101-57-5	-	Aquatic Chronic 2: H411	1-3%

DIISOPROPYLNAPHTHALENE ISOMERS - REACH registered number(s): 01-2119565150-48-####

254-052-6	38640-62-9	-	Asp. Tox. 1: H304; Aquatic Chronic 1: H410	<1%
-----------	------------	---	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact. There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

Eye contact: There may be irritation and redness. There may be severe pain. The eyes may water profusely.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

[cont...]

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Hazardous ingredients:

N-BUTYL-2-(1-ETHYLPENTYL)-1,3-OXAZOLIDINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	29.4 mg/m ³	Workers	-
DNEL	Dermal (repeated dose)	16.7 mg/kg bw/day	Workers	-
DNEL	Inhalation (repeated dose)	6.25 mg/m ³	General Population	-
DNEL	Dermal (repeated dose)	8.3 mg/kg bw/day	General Population	-
DNEL	Oral (repeated dose)	4.2 mg/kg bw/day	General Population	-
PNEC	Fresh water	0.0064 mg/L	-	-
PNEC	Marine water	0.00064 mg/L	-	-
PNEC	Fresh water sediments	1.047 mg/kg sediment	-	-
PNEC	Marine sediments	0.1047 mg/kg sediment	-	-
PNEC	Soil (agricultural)	0.3029 mg/kg soil dw	-	-

DIISOPROPYLNAPHTHALENE ISOMERS

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	30 mg/m ³	Workers	Systemic
DNEL	Dermal (repeated dose)	4.3 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	7.4 mg/m ³	General Population	Systemic
DNEL	Dermal (repeated dose)	2.1 mg/kg bw/day	General Population	Systemic
DNEL	Oral (repeated dose)	2.1 mg/kg bw/day	General Population	Systemic
PNEC	Fresh water	0.26 µg/L	-	-
PNEC	Marine water	0.026 µg/L	-	-
PNEC	Fresh water sediments	0.94 mg/kg sediment	-	-
PNEC	Marine sediments	0.094 mg/kg sediment	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. BS EN 374:2003 / EN ISO 374-1:2016

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community environmental legislation.

Section 9: Physical and chemical properties

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Various
Odour: Characteristic odour
Evaporation rate: Negligible
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Not miscible
Viscosity: Viscous
Boiling point/range°C: No data available. **Melting point/range°C:** No data available.
Flammability limits %: lower: No data available. **upper:** No data available.
Flash point°C: No data available. **Part.coeff. n-octanol/water:** No data available.
Autoflammability°C: No data available. **Vapour pressure:** No data available.
Relative density: No data available. **pH:** No data available.
VOC g/l: No data available.

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact. There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

[cont...]

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 6

Eye contact: There may be irritation and redness. There may be severe pain. The eyes may water profusely.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms. Harmful to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Physico-chemical treatment not specified elsewhere in this Annex which results in final compounds or mixtures which are discarded by means of any of the other possible disposal operations (e.g. evaporation, drying, calcination, etc.).

Recovery operations: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

[cont...]

SAFETY DATA SHEET
VUBA RESIN BOUND PART A

Page: 7

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.