

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 1

Compilation date: 03/10/2018

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** VUBA RESIN BOUND PART B

**Product code:** VBP.118(B)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Vuba Building Products Limited  
Units B3-B4 Grovehill Industrial Estate  
Annie Reed Road  
Beverley  
HU17 0LF  
United Kingdom

**Tel:** +44 (0) 1482 778 897

**Email:** buildingproducts@vuba-group.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0) 1482 778 897  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317

**Most important adverse effects:** May cause an allergic skin reaction. Harmful if inhaled. May cause respiratory irritation.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H317: May cause an allergic skin reaction.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.

**Hazard pictograms:** GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P260: Do not breathe vapours.  
P280: Wear protective gloves/protective clothing/eye

[cont...]

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 2

protection/face protection.

P285: In case of inadequate ventilation wear respiratory protection.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P502: Refer to manufacturer or supplier for information on recovery or recycling.

### 2.3. Other hazards

**Other hazards:** On contact with water carbon dioxide is released.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER - REACH registered number(s): 01-2119485796-17-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
931-274-8	-	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	>90%

HEXAMETHYLENE-DI-ISOCYANATE

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%
-----------	----------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

[cont...]

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 3

An itchy rash may occur at the site of contact. Irritation or pain may occur at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely. There may be severe pain.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation. There may be vomiting and diarrhoea. Blood may be vomited.

**Inhalation:** Exposure may cause coughing or wheezing. There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur. There may be tightness of the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Carbon dioxide. Alcohol or polymer foam. Alcohol resistant foam. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 4

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of mists in the air. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No special requirement.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**HEXAMETHYLENE-DI-ISOCYANATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

**DNEL/PNEC Values**

**Hazardous ingredients:**

**HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (Acute)	0.5 mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation (Chronic)	1 mg/m <sup>3</sup>	Workers	Local
PNEC	Fresh water	0.127 mg/L	-	-
PNEC	Marine water	0.013 mg/L	-	-
PNEC	Fresh water sediments	266 701 mg/kg sedime	-	-
PNEC	Marine sediments	26 670 mg/kg sedimen	-	-

[cont...]

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 5

PNEC	Soil (agricultural)	53 183 mg/kg soil dw	-	-
------	---------------------	----------------------	---	---

**HEXAMETHYLENE-DI-ISOCYANATE**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	0.035 mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation	0.07 mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation (repeated dose)	0.035 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	0.07 mg/m <sup>3</sup>	Workers	Systemic
PNEC	Fresh water	0.0774 mg/L	-	-
PNEC	Marine water	0.000774 mg/L	-	-

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Impermeable gloves. Gloves (solvent-resistant). Breakthrough time of the glove material > 2 hours. BS EN 374:2003 / EN ISO 374-1:2016

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Refer to specific Member State legislation for requirements under Community environmental legislation.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Not miscible

**Viscosity:** Viscous

**Kinematic viscosity:** 600 mPa.s

**Boiling point/range°C:** > 220

**Melting point/range°C:** -20

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** 228

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** ca. 440

**Vapour pressure:** < 0.00001 hPa

**Relative density:** 1.13 g/ml

**pH:** No data available.

**VOC g/l:** No data available.

**9.2. Other information**

**Other information:** Not applicable.

[cont...]

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

**HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER**

DERMAL	RAT	LD50	> 2000	mg/kg
DERMAL	RBT	LD50	> 2000	mg/kg
ORAL	RAT	LD50	> 2500	mg/kg

**HEXAMETHYLENE-DI-ISOCYANATE**

IVN	MUS	LD50	5600	µg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	µl/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact. There may be redness or whiteness of the skin in the area of exposure. An itchy rash may occur at the site of contact. Irritation or pain may occur at the site of contact.

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 7

**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
There may be severe pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.  
Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation. There may be vomiting and diarrhoea. Blood may be vomited.

**Inhalation:** Exposure may cause coughing or wheezing. There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur. There may be tightness of the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

Danio rerio (zebra fish)	96H LC50	22	mg/l
Daphnia magna	48H EC50	> 100	mg/l
Scenedesmus Subspicatus	72H ErC50	> 77.4	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Biological treatment not specified elsewhere which results in final compounds or mixtures which are discarded by means of any of the other possible disposal operations. Physico-chemical treatment not specified elsewhere in this Annex which results in final compounds or mixtures which are discarded by means of any of the other possible disposal operations (e.g. evaporation, drying, calcination, etc.).

[cont...]

**SAFETY DATA SHEET**  
VUBA RESIN BOUND PART B

Page: 8

**Recovery operations:** Not applicable.

**Waste code number:** 08 02 99

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

#### Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

#### Section 15: Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

##### 15.2. Chemical Safety Assessment

#### Section 16: Other information

##### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H332: Harmful if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.